

white duck feather 2-4cm

IDFL # 20-310303

Zhejiang Samsung Down Co., Ltd Wed 10 June 2020

linda@samsungdown.com

aawsamsangaown.com


Arrival Date: Fri 5 June 2020
Report Date: Wed 10 June 2020

Zhejiang Samsung Down Co., Ltd No.288, Xiaoshao East Road, Xintang Street, Xiaoshan District, Hangzhou, Zhejiang 311201

Linda Shen

Sample Type: Plumage Shipped By: By Hand

Sample Identification: white duck feather 2-4cm



¹ CMA Accredited

² CNAS Accredited

This analysis represents (within normal testing variances) the test results from the sample(s) submitted. The analysis may not represent the entire lot, batch or production run. In no event shall IDFL be responsible or liable for any direct, indirect, punitive, incidental, special, or consequential damages whatsoever arising out of or connected with the use of, misuse of, or reliance upon such results or analysis. This test report is subject to the Terms and Conditions found at www.idfl.com.

IDFL LABORATORY AND INSTITUTE

IDFL SALT LAKE 1455 South 1100 East Salt Lake City, UT 84105 USA +1 801 467 7611

info@idfl.com

IDFL EUROPE AG Zürcherstrasse 282 CH-8500 Frauenfeld Switzerland +41 52 765 1574 europe@idfl.com IDFL CHINA
Tonghui Mid-Road 688, Xiaoshan
Hangzhou Zhejiang 311200
China
+86 571 8273 6561
china@idfl.com

IDFL TAIPEI 2F., No. 163 Sec. 2, Wenhua Rd. Banqiao District, New Taipei City Taiwan +886 2 2259 1178

taiwan@idfl.com

Approved By www.idfl.com Client 2313 XS Sample 5 of 5

Page 1 of 4



IDFL # 20-310303

Zhejiang Samsung Down Co., Ltd Wed 10 June 2020

white duck feather 2-4cm

Test Orders Summary					
Test	Test Component	Result	Expected Value		
Content EN 12131 2018	Total Down	2.9%			
Species Down & Feathers IDFB Part 12 2013	Total Goose	0%			
	Total Duck	100%			
Fill Power -Tumble Dry Conditioning EN 12130-B 2018	Final Fill Power Height	81 mm/30g			
Oxygen Number EN 1162 1996	Oxygen	1.6 mg/100g			
Turbidity EN 1164 1998	Turbidity Glass Tube	1000 mm			

This analysis represents (within normal testing variances) the test results from the sample(s) submitted. The analysis may not represent the entire lot, batch or production run. In no event shall IDFL be responsible or liable for any direct, indirect, punitive, incidental, special, or consequential damages whatsoever arising out of or connected with the use of, misuse of, or reliance upon such results or analysis. This test report is subject to the Terms and Conditions found at www.idfl.com.

IDFL LABORATORY AND INSTITUTE

IDFL SALT LAKE 1455 South 1100 East Salt Lake City, UT 84105 USA +1 801 467 7611 info@idfl.com IDFL EUROPE AG
Zürcherstrasse 282
CH-8500 Frauenfeld
Switzerland
+41 52 765 1574
europe@idfl.com

IDFL CHINA
Tonghui Mid-Road 688, Xiaoshan
Hangzhou Zhejiang 311200
China
+86 571 8273 6561
china@idfl.com

IDFL TAIPEI
2F., No. 163 Sec. 2, Wenhua Rd.
Banqiao District, New Taipei City
Taiwan
+886 2 2259 1178

taiwan@idfl.com

Approved By www.idfl.com Client 2313 XS Sample 5 of 5

Page 2 of 4

 $^{^{1}}$ CMA Accredited

² CNAS Accredited



IDFL # 20-310303

Zhejiang Samsung Down Co., Ltd Wed 10 June 2020

white duck feather 2-4cm

Content EN 2	12131 2018 ^{2, 1}
Down Clusters	2.8%
Down Fibers	0.1%
Waterfowl Feather Fibers	0.3%
Waterfowl Feathers	95.0%
Broken and Damaged Waterfowl Feathers	1.4%
Quill	0.0%
Landfowl	0.0%
Residue	0.4%
Total	100.0%
Describée) Head for Evoluction	
Result(s) Used for Evaluation	
Total Down Down Fiber Allowance (0.1%)	2.9%
+ Down Clusters (2.8%)	
Total Waterfowl Feathers	96.7%
Waterfowl Feather Fibers & Broken and Damaged Waterfowl Feathers	
Allowance (1.7%) + Warerfowl Feathers (95.0%)	
Other Elements	0.4%
Excess Down Fiber (0.0%)	0.470
+ Excess Waterfowl Feather Fibers & Broken and Damaged Waterfowl	
Feathers (0.0%) + Landfowl (0.0%)	
+ Residue (0.4%)	
+ Quill (0.0%)	
Species Down & Feath	ers IDFB Part 12 2013 ^{2, 1}
Goose Down	0%
Duck Down	100%
Goose Feathers	0%
Duck Feathers	100%
Total Goose	0%
Total Duck	100%
Fill Power -Tumble Dry Cor	nditioning EN 12130-B 2018 ²
Height	81 mm/30g
Volume	178 cm³/g
Fill Power - Steam Condi	itioning EN 12130-A 2018 ²
Volume	365 in³/30g
Oxygen Number	EN 1162 1996 ^{2, 1}
Oxygen	1.6 mg/100g

 $^{^{1}}$ CMA Accredited

This analysis represents (within normal testing variances) the test results from the sample(s) submitted. The analysis may not represent the entire lot, batch or production run. In no event shall IDFL be responsible or liable for any direct, indirect, punitive, incidental, special, or consequential damages whatsoever arising out of or connected with the use of, misuse of, or reliance upon such results or analysis. This test report is subject to the Terms and Conditions found at www.idfl.com.

IDFL LABORATORY AND INSTITUTE

IDFL SALT LAKE 1455 South 1100 East Salt Lake City, UT 84105 USA +1 801 467 7611

info@idfl.com

IDFL EUROPE AG Zürcherstrasse 282 CH-8500 Frauenfeld Switzerland +41 52 765 1574 europe@idfl.com IDFL CHINA
Tonghui Mid-Road 688, Xiaoshan
Hangzhou Zhejiang 311200
China
+86 571 8273 6561

china@idfl.com

IDFL TAIPEI 2F., No. 163 Sec. 2, Wenhua Rd. Banqiao District, New Taipei City Taiwan +886 2 2259 1178

taiwan@idfl.com

Approved By www.idfl.com Client 2313 XS Sample 5 of 5

Page 3 of 4

² CNAS Accredited



IDFL # 20-310303

Zhejiang Samsung Down Co., Ltd Wed 10 June 2020

white duck feather 2-4cm

Turbidity EN 1164 1998 ^{2, 1}

Turbidity Glass Tube 1000 mm

> Turbidity NTU 1.96 NTU

European Standards Down & Feather Products Labelling EN 12934

Evaluation Component	Test	Test Component	Requirement	Result	Finding
Basic -	Oxygen Number EN 1162 1996	Oxygen Number	Max 20 mg/100g	1.6 mg/100g	Pass
	Turbidity EN 1164 1998	Turbidity	Greater than 300 mm	1000 mm	Pass
100% Waterfowl Feathers Content EN 12131 2018	Total Down	Min 0%	2.9%	Pass	
	Other Elements	N/A %	0.4%	-	
	Down Clusters	Min 0%	2.8%	Pass	
	Landfowl	Max 9.9%	0.0%	Pass	
Class I	Content EN 12131 2018	Other Elements	Max 5%	0.4%	Pass
Duck (Down & Feathers)	Species Down & Feathers IDFB Part 12 2013	Total Duck	Min 70	100	Pass
Fill Power Steam (in³/30g)	Fill Power - Steam Conditioning EN 12130-A 2018	Fill Power Steam (in³/30g)		365 in³/30g	-
Fill Power Tumble Dry (cm³/g)	Fill Power -Tumble Dry Conditioning EN 12130-B 2018	Fill Power Tumble Dry (cm³/g)		178 cm³/g	-

Total Down: Down Fiber Allowance (0.1%) + Down Clusters (2.8%) = 2.9%

Total Waterfowl Feathers:

Waterfowl Feather Fibers & Broken and Damaged Waterfowl Feathers Allowance (1.7%) + Waterfowl Feathers (95.0%)

= 96.7%

Other Elements:

Excess Down Fiber (0.0%) + Excess Waterfowl Feathers & Broken and Damaged Waterfowl Feathers (0.0%) + Landfowl (0.0%) + Residue (0.4%) + Quill (0.0%)

= 0.4%

Suggested Label based on EN 12934 requirements

New Pure Duck Feathers Class I, 100% Feathers

The decision rules found in the test standard EN 12934:1999 fall within the measure of uncertainty as referenced in the relevant test standards

¹ CMA Accredited

info@idfl.com

² CNAS Accredited

This analysis represents (within normal testing variances) the test results from the sample(s) submitted. The analysis may not represent the entire lot, batch or production run. In no event shall IDFL be responsible or liable for any direct, indirect, punitive, incidental, special, or consequential damages whatsoever arising out of or connected with the use of, misuse of, or reliance upon such results or analysis. This test report is subject to the Terms and Conditions found at www.idfl.com.

IDFL LABORATORY AND INSTITUTE

IDFL SALT LAKE 1455 South 1100 East Salt Lake City, UT 84105 +1 801 467 7611

IDFL EUROPE AG Zürcherstrasse 282 CH-8500 Frauenfeld Switzerland +41 52 765 1574 europe@idfl.com

IDFL CHINA Tonghui Mid-Road 688, Xiaoshan Hangzhou Zhejiang 311200 China +86 571 8273 6561 china@idfl.com

IDFL TAIPEI

taiwan@idfl.com

2F., No. 163 Sec. 2, Wenhua Rd. Banqiao District, New Taipei City Taiwan +886 2 2259 1178

Approved By www.idfl.com Client 2313 Sample 5 of 5

Page 4 of 4